

Canton Movie CD 102

Technical Data **New**

Type	Home-Cinema-System with active subwoofer system
Engineering Principle	Front: 2-way closed system Center: 2-way closed system Surround: 2-way closed system Subwoofer: Bandpass system
Music power handling	Front: 100 watts Center: 100 watts Surround: 100 watts
Nominal/musical output	Subwoofer: 100 watts
SPL (1 watt/1m)	86 db (1 W, 1 m)
Frequency response	Front: 80...25.000 Hz Center: 80...25.000 Hz Surround: 80...25.000 Hz Subwoofer: 33...140 Hz
Crossover frequency	Front: 3.900 Hz Center: 3.900 Hz Surround: 3.900 Hz Subwoofer: 80...140 Hz (adjustable)
Woofer	Front: 1 x 80 mm (3"), aluminum Center: 2 x 80 mm (3"), aluminum Surround: 1 x 80 mm (3"), aluminum Subwoofer: 1 x 200 mm (8"), Cellulose/graphite (Wave surround)
Tweeter	Front: 1 x 15 mm (1"), aluminum Center: 15 mm (1"), aluminum Surround: 15 mm (1"), aluminum
Nominal Impedance	4...8 ohms
Dimensions (WxHxD)	Front: 9 x 13.5 x 10 cm (3.5" x 5.3" x 3.9") Center: 22 x 9 x 10 cm (8.7" x 3.5" x 3.9") Surround: 9 x 13.5 x 10 cm (3.5" x 5.3" x 3.9") Subwoofer: 24 x 42.5 x 42 cm (9.4" x 16.7" x 16.5")
Weight	Front: 1.0 kg Center: 1.7 kg Surround: 1.0 kg

	Subwoofer: 10.4 kg
Available accessories	Loudspeaker stand LS 90 Loudspeaker stand LS 95
Special Features	<p>Front: Magnetically shielded Polyswitch protection Wall brackets included</p> <p>Center: Magnetically shielded</p> <p>Surround: Magnetically shielded Polyswitch protection Wall brackets included</p> <p>Subwoofer: Adjustable crossover frequency Adjustable bass level SC-technology</p>