

## Canton Movie CD 202 - Specifications

### Technical Data **New**

Type	Home-Cinema-System with active subwoofer system
Engineering Principle	Front: 2-way closed system Center: 2½-way closed system Surround: 2-way closed system Subwoofer: Bass reflex system
Music power handling	Front: 120 watts Center: 130 watts Surround: 120 watts
Nominal/musical output	Subwoofer: 150 watts
SPL (1 watt/1m)	87 db (1 W, 1 m)
Frequency response	Front: 45...30.000 Hz Center: 45...30.000 Hz Surround: 45...30.000 Hz Subwoofer: 25...200 Hz
Crossover frequency	Front: 3.900 Hz Center: 400 / 3.500 Hz Surround: 3.900 Hz Subwoofer: 55...200 Hz (adjustable)
Woofers	Front: 1 x 110 mm (4"), aluminum Center: 1 x 110 mm (4"), aluminum Surround: 1 x 110 mm (4"), aluminum Subwoofer: 1 x 220 mm (9"), aluminum
Midrange	Center: 1 x 110 mm (4"), aluminum
Tweeter	Front: 1 x 25 mm (1"), aluminum Center: 25 mm (1"), aluminum Surround: 25 mm (1"), aluminum
Nominal Impedance	4...8 ohms
Dimensions (WxHxD)	Front: 14 x 22 x 10 cm (5.5" x 8.7" x 3.9") Center: 43 x 14 x 10 cm (16.9" x 5.5" x 3.9") Surround: 14 x 22 x 10 cm (5.5" x 8.7" x 3.9") Subwoofer: 25.5 x 45 x 37 cm (10" x 17.7" x 14.6")

Weight	Front: 2.0 kg Center: 3.5 kg Surround: 2.0 kg Subwoofer: 12.1 kg
Available accessories	Loudspeaker stand LS 105
Special Features	Front: Magnetically shielded Polyswitch protection Wall brackets included  Center: Magnetically shielded  Surround: Magnetically shielded Polyswitch protection Wall brackets included  Subwoofer: Adjustable crossover frequency Adjustable bass level SC-technology